



Professional Keyboard Amplifier

SS-150K



SSK-250E



SPECIFICATIONS :

SS-150K

Amplifier:
 Hi-Fi output (8 Q) power : 80W
 T.H.D : 0.5%(10W 8Q IKHz)
 Frequency response : 20Hz-20KHz(±2dB)
 S/N ratio : 76dB(A weight)
 MIC sensitivity : 15mV 600
 Signal sensitivity : 250mV 22K
Speaker :
 Speaker unit : 15" single magnet bass, 26cores
 treble horn
 rated power : 120W(30--180W)
 Impedance : 4
 Frequency response : 50Hz-16KHz(±3dB)
 Feature sensitivity : 91 dB/I W I M

SSK-250E

Amplifier part:
 Audio output power : 500W(4 ohm)
 Rated power : 250W (4 ohm)
 Frequency band : 20Hz-20kHz (±2dB)
 Signal/Noise ratio (with IHF A Fiter) : 76dB
 CH1, CH2, CH3 MIC input sensitivity : 15mV600
 Ch4 Signal sensitivity : 250mV 22K sZ
 Power source : ~220V 50Hz
 Weight : 25kg
 Measurement: (mm) : 680 (W) X 350 (H) X 620 (D)
Sound box part:
 Speaker cell : 15 inches woofer+26 cores
 clarion treble
 rating power : 250W(30W~300W)
 Impedance : 4
 Frequency band : 75Hz-17kHz (±3dB)
 Characteristic sensitivity : 93dB/1m1w

Rear Panel

SS-150K



SSK-250E

