



Professional Wire/Wireless Microphone System



OS - 08

Product Features :

OS - 08

1. COMPREHENSIVE PERFORMANCE

CARRIER FREQUENCY : UHF700 ~ 870MHz  
 FREQUENCY STABILIZATION : LESS THAN ± 30ppm  
 DYNAMIC RANGE : MORE THAN 90dB  
 TOTAL HARMONIC DISTORTION : LESS THAN 0.5%  
 FREQUENCY RESPONSE : 40HZ--15KHZ ± 3dB  
 AUDIO OUTPUT LEVEL : SEPARATE TYPE : 0-- ± 400mV

MIX TYPE : 0-- ± 200mV

2. HANDLING MICROPHONE

TRANSMITTER POWER : 8mW  
 MODULATION TYPE : FM,F3F  
 MAX DEVIATION : ± 45Khz  
 SPURIOUS EMISSION : MORE THAN 40dB(WITH CARRIER)  
 BATTERY VOLTAGE : 3Volt (1.5V AAx2) battery  
 CONTINUOUS USING : 6 hours

3. FIXED RECEIVER

POWER SUPPLY : AC 220V 50/60Hz  
 CONSUME POWER : 4 Watt  
 SIGNAL/NOISE RATIO : MORE THAN 90DB  
 IMAGE & SPURIOUS REJECTION : MORE THAN 80db  
 BORDER UPON CHANNEL REJECTION : MORE THAN 80db  
 RECEIVING SENSITIVITY : 10dBuV(SINAD=30dB)  
 DE-EMPHASIS : 50us

Dimension

OS - 08

