



Professional Wired/Wireless Microphone System



ULS - 8 H

1. COMPREHENSIVE PERFORMANCE

CARRIER FREQUENCY : UHF700 ~ 870MHz
 FREQUENCY STABILIZATION : LESS THAN ± 30ppm
 DYNAMIC RANGE : MORE THAN 90dB
 TOTAL HARMONIC DISTORTION : LESS THAN 0.5%
 FREQUENCY RESPONSE : 40HZ--15KHZ ± 3dB
 AUDIO OUTPUT LEVEL : SEPARATE TYPE : 0-- ± 400mV

MIX TYPE : 0-- ± 200mV

2. HANDLING MICROPHONE

TRANSMITTER POWER : 8mW
 MODULATION TYPE : FM,F3F
 MAX DEVIATION : ± 45Khz
 SPURIOUS EMISSION : MORE THAN 40dB(WITH CARRIER)
 BATTERY VOLTAGE : 3Volt (1.5V AAx2) battery
 CONTINUOUS USING : 6 hours

3. FIXED RECEIVER

POWER SUPPLY : AC 220V 50/60Hz
 CONSUME POWER : 4 Watt
 SIGNAL/NOISE RATIO : MORE THAN 90DB
 IMAGE & SPURIOUS REJECTION : MORE THAN 80db
 BORDER UPON CHANNEL REJECTION : MORE THAN 80db
 RECEIVING SENSITIVITY : 10dBuV(SINAD=30dB)
 DE-EMPHASIS : 50us

Dimension

ULS - Series

