



Professional Wired/Wireless Microphone System



VLS - 8 H

SPECIFICATIONS

VLS - 8 H

1. COMPREHENSIVE PERFORMANCE

CARRIER FREQUENCY : VHF170 ~ 280MHz
 FREQUENCY STABILIZATION : LESS THAN ± 30 ppm
 DYNAMIC RANGE : MORE THAN 90dB
 TOTAL HARMONIC DISTORTION : LESS THAN 0.5%
 FREQUENCY RESPONSE : 40HZ--15KHZ ± 3 dB
 AUDIO OUTPUT LEVEL : SEPARATE TYPE : 0-- ± 200 mV

2. HANDLING MICROPHONE

TRANSMITTER POWER : 8mW
 MODULATION TYPE : FM, F3F
 MAX DEVIATION : ± 25 Khz
 SPURIOUS EMISSION : MORE THAN 40dB(WITH CARRIER)
 BATTERY VOLTAGE : 9 Volt battery
 CONTINUOUS USING : 6 hours

2. FIXED RECEIVER

POWER SUPPLY : AC 220V 50/60Hz
 CONSUME POWER : 4 Watt
 SIGNAL/NOISE RATIO : MORE THAN 90dB
 IMAGE & SPURIOUS REJECTION : MORE THAN 80db
 BORDER UPON CHANNEL REJECTION : MORE THAN 80db
 RECEIVING SENSITIVITY : 10dBuV(SINAD=30dB)
 DE-EMPHASIS : 50us

VLS - 8 H

Dimension

