



### Professional Active Loudspeaker System

OS 15 A - 350



### Product Features :

- |                      |  |
|----------------------|--|
| Type                 | : Plastic powered fullrange loudspeaker system                               |
| Enclosure            | : Two Way System   |
| Components           | : Lf 1 x 15 " , Woofer Bass Reflex,<br>Hf 1 x 1" high transducers voice coil |
| Frequency response   | : 50 Hz - 16 Khz   |
| Pressure Sensitivity | : 1 W@1m : 95 dB, peak spl : 126 dB  |
| Dispersion           | : Horizontal x Vertical 100 degrees  |
| Handling             | : Two transport handles and stand adapter                                    |
| Power Output         | : 2 ch LF: 300W HF : 50W   |
| Power Consumption    | : 250 w,   |
| Processor controll   | : 1 x gain - volume - Hi - mid - control with swich for music or vocal       |
| Input Connection     | : 1 x Neutrik Combo (XLR+Jack)<br>1 x XLR Loop Thru                          |
| Power supply         | : 220V/50HZ-60 Hz / 10 A Fuse  |
| Input connection     | : 2 x XLR Loup Thru  |
| Dispersion           | : Horizontal x vertical 100 degrees  |
| weight kg            | : 29   |

### Dimension

OS 15 A-350

